
# Fidelius: Protecting User Secrets from Compromised Browsers


Saba Eskandarian, Jonathan Cogan, Sawyer Birnbaum, Peh Chang Wei Brandon, Dillon Franke, Forest Fraser, Gaspar Garcia, Eric Gong, Hung T. Nguyen, Taresh K. Sethi, Vishal Subbiah, Michael Backes, Giancarlo Pellegrino, Dan Boneh






## In Browsers we Trust





## In Browsers we Trust

C Bank of America Corporation (US) https://www.bankofamerica.com/




My TurboTax® Login - S × +

## Hardware Enclaves


A trusted component in an untrusted system

- Protected memory isolates enclave from compromised OS
- Proves authenticity via attestation
- Enclaves in our implementation use Intel SGX




# Challenges

1. Enclave only interacts with outside world through OS




# Challenges

2. Browsers have a LOT of code and many bugs/vulnerabilities.




# Challenges


Browsers have a LOT of code and many bugs/vulnerabilities.
 Vulnerable code in enclave → super-malware!




Goal: protect user keyboard inputs to browser from fully compromised OS




Keeps browser outside of hardware enclave





Support for HTML forms, simple JavaScript, local storage, and **XmlHttpRequests User Computer** Enclave -Data -Secrets -Fidelius









Trusted path from enclave to secure I/O devices



#### Minimal changes for developers





- -Data
- -Secrets
- -Fidelius







#### Trusted Path to/from Enclave

Keyboard/display dongles built from Raspberry Pls

Dongles switch between trusted/untrusted modes




## Trusted Path to/from Enclave

Keyboard/display dongles built from Raspberry Pls

Dongles switch between trusted/untrusted modes

Keyboard: encrypt keystrokes at constant rate






## Trusted Path to/from Enclave


Keyboard/display dongles built from Raspberry Pls

Dongles switch between trusted/untrusted modes

Keyboard: encrypt keystrokes at constant rate

Display: decrypt overlays sent by enclave









## Fidelius for Users

Security indicator lights for keyboard and display






Schechter and Dhamija, The Emperor's New Security Indicators. S&P 2007.

Whalen and Inkpen, Gathering Evidence: Use of Visual Security Cues in Web Browsers. Gl 2005.

## Fidelius for Users

Security indicator lights for keyboard and display

Green overlay verifies who gets data and what data you are giving





Schechter and Dhamija, The Emperor's New Security Indicators. S&P 2007.


Whalen and Inkpen, Gathering Evidence: Use of Visual Security Cues in Web Browsers. Gl 2005.

## Fidelius for Users

Security indicator lights for keyboard and display

Green overlay verifies who gets data and what data you are giving

Security relies on users watching indicators (in our prototype)






Schechter and Dhamija, The Emperor's New Security Indicators. S&P 2007.

Whalen and Inkpen, Gathering Evidence: Use of Visual Security Cues in Web Browsers. GI 2005.

# Example


User view (photograph)

Malware view (screen capture)



## What Fidelius Does

- Secure user I/O against tampering, eavesdropping, replay, etc.
- Give trusted Javascript local access to sensitive data
- Only allow data to be sent to designated destination





#### What Fidelius Does Not Do

Secure hardware enclave against side-channel attacks
 [XCP'15,GESM'17,BMD+'17,WKPK'17,LSG+'17,CCX+'18,BMW+'18]

#### What Fidelius Does Not Do

- Secure hardware enclave against side-channel attacks
  [XCP'15,GESM'17,BMD+'17,WKPK'17,LSG+'17,CCX+'18,BMW+'18]
- Protect against dumb web sites







TCB: ~8,500 lines of C++

TCB: ~8,500 lines of C++

#### **Display Latency Scaling**

Doubling trusted display size only slightly increases display latency

Field size(s)	W	Н	W×H px	Time (ms)	Incr. (ms)
1 Small	171	50	8,550	195.83	
1 Medium	342	50	17,100	199.20	3.38
1 Large	683	50	34,150	209.65	10.45
1 Extra large	911	50	45,550	214.74	-
2 Extra large	911	100	91,100	227.02	12.28

TCB: ~8,500 lines of C++

#### **Display Latency Scaling**


Doubling trusted display size only slightly increases display latency

#### **Display Bottlenecks**

Expensive Render/Refresh due to implementation hacks, easily improvable

Field size(s)	W	Н	W×H px	Time (ms)	Incr. (ms)
1 Small	171	50	8,550	195.83	-
1 Medium	342	50	17,100	199.20	3.38
1 Large	683	50	34,150	209.65	10.45
1 Extra large	911	50	45,550	214.74	-
2 Extra large	911	100	91,100	227.02	12.28

#### Fidelius Display Pipeline Costs



TCB: ~8,500 lines of C++

#### **Display Latency Scaling**


Doubling trusted display size only slightly increases display latency

#### <u>Display Bottlenecks</u>

Expensive Render/Refresh due to implementation hacks, easily improvable

Field size(s)	W	Н	W×H px	Time (ms)	Incr. (ms)
1 Small	171	50	8,550	195.83	-
1 Medium	342	50	17,100	199.20	3.38
1 Large	683	50	34,150	209.65	10.45
1 Extra large	911	50	45,550	214.74	-
2 Extra large	911	100	91,100	227.02	12.28

#### Fidelius Display Pipeline Costs




#### **Display Latency**

(Unoptimized) refresh rate 2.8x faster than latest Kindle

Speed due to only sending small overlay rather than encrypting full display

Graph shows latency for Fidelius rendering a username/password login form



# Summary

Fidelius uses enclave to protect user secrets even if entire OS compromised

Support for forms, JS, persistent local storage, and XmlHttpRequests

Trusted path to enclave for user I/O (other projects welcome to use)

https://crypto.stanford.edu/fidelius https://github.com/SabaEskandarian/Fidelius

